

VS905 Value Series RO Faucet

Features:

- 1/4-turn ceramic disk valve, engineered plastic housing
- Available with or without an air gap
- 36" preinstalled 1/4" inlet tubing
- Lead-free plastic water passages
- Plated zinc alloy outer body
- 3" inlet shank, 7/16"-24 threads
- Spout reach is approximately 5-1/2" (140 mm)
- Pressure rating: 125 PSI/8.3 BAR.
- Flow rate: 1.0 gpm/3.785 lpm at 35 PSI/2.32 BAR.
- Temperature rating: 40°F/4°C to 158°F/70°C.
- Lead-free brass gooseneck spout swivels 360 degrees
- High polished chrome-plated finish standard
- Satin nickel finish available
- Includes installation hardware and instructions

Colors/Finishes:

- 1022292 - Polished Chrome
- 1022293 - Polished Chrome with air gap
- 1022294 - Satin Nickel
- 1022295 - Satin Nickel with air gap

Technical dimensions on reverse side.

Codes Applicable:

The VS905 Value Series RO Faucet is certified to NSF/ANSI Std. 61 - 9 & 372. These Value Series RO Faucets are low-lead plumbing products and are in compliance with California's Health and Safety Code (Section 116875; commonly known as AB1953).

- ADA Compliance - ANSI A117.1
- Complies with the U.S. Safe Drinking Water Act of 2014.

Technical dimensions on reverse side.

tomlinson[®]

www.tomlinsonind.com



