

# 600 UCBR Series Ultra Contemporary RO Faucet



## Features:

- Retrofits most brands
- Smooth operating ceramic disk element
- Lever style handle
- High reach neck design of 12-5/8" (321 mm)
- Neck swivels 360°
- Protective spout tip prevents after drip
- Patented modular air gap (U.S. patent #7,011,106)
- Base diameter is 2-1/4" (57 mm)
- Two year warranty
- Spout reach is approximately 6" (153 mm)
- Pressure rating: 125 PSI/8.6 BAR
- Flow rate: 1.0 gpm/3.785 lpm at 35 PSI/2.32 BAR
- Temperature rating: 40°F/4°C to 150°F/66°C
- 1/4" OD x 30" tubing pre-installed
- Includes installation hardware and instructions

## Colors/Finishes:

- Polished chrome (#1024852)
- Satin nickel (#1025111)
- Antique bronze (#1025115)
- Venetian Bronze (#1025112)
- Brushed Stainless (#1025114)

## Common Replacement Parts:

- Cartridge (#1917362)

Technical dimensions on reverse side.

## Codes Applicable:

● The 600 UCBR Series Ultra Contemporary RO Faucet is certified to NSF/ANSI Standard 61 – 9 & 372. These Ultra Contemporary RO Faucets are low-lead plumbing products and are in compliance with California's Health and Safety Code (Section 116875; commonly known as AB1953).

● Compliant with the USEPA Safe Drinking Water Act effective January 4, 2014.

● ADA Compliance - ANSI A117.1

Technical dimensions on reverse side.

[www.tomlinsonind.com](http://www.tomlinsonind.com)



